



P81000 Phase Rotation Detector



PRODUCT FEATURES

- 3-phase rotation detection: normal phase, reverse phase and phase deficiency
- Functionality options include detection of live wires, simple power, fire-wire, breakpoint location, DC line break and line maintenance
- Dynamic LED display
- Magnetic base plate footings allow temporary mounting to metal surfaces
- Power-saving performance with maximum rated power of 100mVA

Want to know more about our Utility Pro Products line or need a quote?

www.sncmfg.com | info@sncmfg.com

Transforming tomorrow.



Phase Rotation Detector



GENERAL CHARACTERISTICS

PART NUMBER

P81000

POWER

AA1.5Vx2

INPUT VOLTAGE

70 - 600VAC

FREQUENCY RANGE

40 - 70 Hz

PRODUCT SIZE

2.75" x 2.95" x 1.18"
(70mm x 75mm x 30mm)

PRODUCT NET WEIGHT

.36 lbs. (164g)

STANDARD INDIVIDUAL PACKAGING



STANDARD QUANTITY PER CARTON

1 pc.

MEASUREMENT OF STANDARD CARTON

7" x 5" x 5"
(177.8mm x 127mm x 127mm)

WEIGHT OF STANDARD CARTON

1.1 lbs. (499g)

SPECIFICATIONS

Power Supply	2 AA batteries
Clamp Wire Size	Diameter \varnothing .06 - \varnothing .63" (\varnothing 1.6 - \varnothing 16mm)
Live Voltage Range	A/C 70 ~ 1000V
Auto Power Off	Meter automatically powers off after 5 minutes of inactivity
Working Temperature	-10 ~ 50°C (14 ~ 122°F); below 80%rh
Storage Temperature	-20 ~ 60°C (-4 ~ 140°F); below 90%rh
LED Display	Positive phase sequence: The four-phase sequence lamps blink in order (clockwise) Negative phase sequence: The four-phase sequence lamps blink in order (counterclockwise) Live voltage indication: L1/L2/L3 lamps light up Default phase: L1/L2/L3 lamps are off Open circuit: L1/L2/L3 lamps are off
Beep	Positive phase sequence: Intermittent short beeps Negative phase sequence: Continuous long beeps
Magnetic Force	Magnetic base plate footings allow temporary mounting to metal surfaces
Clamp Lead Length	1.96' (0.6m)
Maximum Measured Voltage	A/C 1000V
Dielectric Strength	5.4kVrms
Maximum Rated Power	300mVA
Safety Provisions	EN61010-1: 2001, EN61010-031: 2002, Pollution level 2, CAT 3 (600V)
Meter Weight	.44 lbs. (200g) with battery
Meter Dimensions	Width, height, thickness 2.75" x 2.95" x 1.18" (70mm x 75mm x 30mm)

Learn more about how our custom solutions
can transform tomorrow's products.



Connect on social:

www.sncmfg.com | 800-558-3325 | info@sncmfg.com

T0622